



**MGL-III-532/1~450mW**

### LD PUMPED ALL-SOLID-STATE GREEN LASER





All solid state 532nm green laser is made features of high output power stability, good beam profile, ultra compact, long lifetime, low cost and easy operating, which is widely used in collimation, laser medical treatment, scientific experiment, optical instrument, laser display, laser lighting show, etc.



#### SPECIFICATIONS

Wavelength (nm)	532 ± 1		
Output power (mW)	>1, 5, 10, 20, ... , 450		
Transverse mode	TEM <sub>00</sub>		
Operating mode	CW		
Power stability (rms, over 4 hours)	<1%, <3%, <5%, <10%		
Warm-up time (minutes)	<10		
M <sup>2</sup> factor	<1.2		
Beam divergence, full angle (mrad)	<1.5		
Beam diameter at the aperture (mm)	~2.0		
Beam height from base plate (mm)	24.8		
Polarization ratio	>100:1 (0 or 90 degree)		
Pointing stability after warm-up (mrad)	<0.05		
Operating temperature (°C)	10~35		
Power supply (90-264VAC or 5VDC)	PSU-III-LED	PSU-III-FDA	PSU-III-OEM
TTL / Analog modulation	Optional, 2kHz or higher (on request, up to 30kHz)		
Expected lifetime (hours)	10000		
Warranty	1 year		



MxL-III-532	PSU-III-LED	PSU-III-FDA	PSU-III-OEM
 140.8(L)×73(W)×46.2(H) mm <sup>3</sup> , 0.6kg	 154 (L) ×155(W) ×95 (H) mm <sup>3</sup> , 1.5kg	 133 (L) ×130(W) ×65 (H) mm <sup>3</sup> , 1.2kg	 100 (L) ×60(W) ×56 (H) mm <sup>3</sup> , 0.2kg
