

MIL-N-1064/4000~5000mW

### LD PUMPED ALL-SOLID-STATE INFRARED LASER AT 1064 nm




All solid state infrared laser at 1064nm is made features of ultra compact, long lifetime, low cost and easy operating, which is used in scientific experiment, optical instrument, optical sensor, measurement, communication, spectrum analysis, etc.



#### SPECIFICATIONS

Wavelength (nm)	1064±1	
Output power (mW)	>4000, 4200, 4400, ... ,5000	
Transverse mode	Near TEM <sub>00</sub>	
Operating mode	CW	
Power stability (rms, over 4 hours)	<1%, <3%, <5%	
Warm-up time (minutes)	<10	
M <sup>2</sup> factor	<3.0	
Beam divergence, full angle (mrad)	<1.5	
Beam diameter at the aperture (mm)	~3.0	
Beam height from base plate (mm)	68.2	
Polarization ratio	>100:1	
Pointing stability after warm-up (mrad)	<0.05	
Operating temperature (°C)	10~35	
Power supply (90-264VAC)	PSU-H-LED	PSU-H-FDA
TTL modulation/ Analog modulation	Optional, 2kHz or higher (others on request, up to 30kHz)	
Expected lifetime (hours)	10000	
Warranty period	1 year	



MxL-N-1064	PSU-H-LED	PSU-H-FDA
 <p>235(L)×99(W)×94(H) mm<sup>3</sup>, 2.6 kg</p>	 <p>240 (L) ×146(W) ×108 (H) mm<sup>3</sup>, 2.6 kg</p>	 <p>238 (L) ×146(W) ×102 (H) mm<sup>3</sup>, 2.3 kg</p>
